

App. No. 10/044,294
Amendment Dated: May 6, 2004
Reply to Office Action of February 6, 2004

Amendments to the Claims:

Claim 1 (currently amended): A system for performing wireless communications, comprising:

a broadcast transmitter configured to transmit broadcast information according to a first transmission type over a subcarrier channel to a wide area on a predetermined schedule;

a localcast transmitter configured to transmit local information according to a second transmission type over a local area, wherein the local area is smaller than the wide area and the first transmission type is different than the second transmission type; and

a mobile device including a receiver, the receiver being configured to receive the broadcast information and the local information.

Claim 2 (withdrawn): A localcast transmitter, comprising:

a first interface;

an encoder coupled to said first interface;

a packet assembler coupled to said encoder;

a control function coupled to said first interface, said encoder and said packet assembler;

a modulator; and

an antenna.

Claim 3 (withdrawn): The localcast transmitter in claim 2, wherein the localcast transmitter is further comprised of a data source for a local area transmission system.

Claim 4 (withdrawn): The localcast transmitter in claim 2, wherein the first interface is further comprised of at least one of a USB-compatible interface, an RS-232 interface, and an IEEE-1394 interface.

Claim 5 (withdrawn): The localcast transmitter in claim 2, wherein the control function collects transmitted packets from a data source and performs handshaking functions.

App. No. 10/044,294
Amendment Dated: May 6, 2004
Reply to Office Action of February 6, 2004

Claim 6 (withdrawn): The localcast transmitter in claim 2, further comprising a second encoder.

Claim 7 (withdrawn): The localcast transmitter in claim 2, wherein the packet assembler further performs the steps of interleaving encoded system information into data segments; adding correlation information to said data segments; and converting said data segments into a bit stream.

Claim 8 (withdrawn): The localcast transmitter in claim 2, wherein the localcast transmitter is further configured to broadcast in a locally-unused portion of the FM band.

Claim 9 (withdrawn): The localcast transmitter in claim 2, further comprising a data source that is further comprised of a personal computer system.

Claim 10 (withdrawn): The localcast transmitter in claim 2, wherein the encoder is further comprised of a first convolutional encoder for system information.

Claim 11 (withdrawn): The localcast transmitter in claim 10, wherein the encoder is further comprised of a second convolutional encoder for data.

Claim 12 (withdrawn): A broadcast transmitter, comprising:
an input-output controller coupled to a first input interface and to a buffer memory;
a control processor coupled to said input-output controller and to a second input interface;
a precision time base coupled to said control processor;
an encoding engine coupled to said input-output controller, said control processor, and to a first memory; and
a subcarrier signal generator, coupled to said encoding engine, said control processor, a second memory, and to a subcarrier output.

App. No. 10/044,294
Amendment Dated: May 6, 2004
Reply to Office Action of February 6, 2004

Claim 13 (withdrawn): The broadcast transmitter in claim 12, wherein the control processor includes at least one of a microprocessor, microcontroller, programmable logic array, programmable gate array, and an ASIC.

Claim 14 (withdrawn): The broadcast transmitter in claim 12, wherein the input-output controller comprises a field-programmable gate array.

Claim 15 (withdrawn): The broadcast transmitter in claim 12, wherein the first input interface further comprises at least one of an RS-422 interface, an RS-232 interface, an IEEE-1394 interface, a USB interface, and an Ethernet interface.

Claim 16 (withdrawn): The broadcast transmitter in claim 12, wherein the second input interface further comprises at least one of an RS-232 interface an RS-422 interface, an RS-232 interface, an IEEE-1394 interface, a USB interface, and an Ethernet interface.

Claim 17 (withdrawn): The broadcast transmitter in claim 12, wherein the precision time base is comprised of a 1-ppm oscillator.

Claim 18 (withdrawn): The broadcast transmitter in claim 12, wherein the subcarrier signal generator is further comprised of a modulator, a digital-analog converter, and an output filter.

Claim 19 (withdrawn): The broadcast transmitter in claim 18, wherein the modulator is further comprised of a field-programmable gate array.

Claim 20 (withdrawn): A mobile device, comprising:
an antenna assembly;
a real-time component comprising:
a system timing function;
a real-time event dispatching function; and

App. No. 10/044,294
Amendment Dated: May 6, 2004
Reply to Office Action of February 6, 2004

a digital radio;
a digital control and processing circuit;
a microcomputer assembly;
a random access memory;
a nonvolatile memory; and
a microprocessor-controlled user interface.

Claim 21 (withdrawn): The mobile device in claim 20, wherein the mobile device is further configured to be worn on a person's wrist.

Claim 22 (withdrawn): The mobile device in claim 21, wherein the mobile device is further configured to display the current time.

Claim 23 (withdrawn): The mobile device in claim 20, wherein the mobile device is further configured to operate within a paging unit.

Claim 24 (withdrawn): The mobile device in claim 20, wherein the mobile device is further configured to operate within a cellular telephone.

Claim 25 (withdrawn): The mobile device in claim 20, wherein the mobile device is further configured to receive information content from a local-area transmitter and from a broadcast transmitter.

Claim 26 (withdrawn): The mobile device in claim 20, further comprising a transceiver.

Claim 27 (withdrawn): The mobile device in claim 26, wherein the mobile device is further configured to transmit and receive information from a second mobile device.

Claim 28 (withdrawn): The mobile device in claim 27, wherein the mobile device is further configured to transmit and receive information from a plurality of mobile devices.

App. No. 10/044,294
Amendment Dated: May 6, 2004
Reply to Office Action of February 6, 2004

Claim 29 (withdrawn): The mobile device in claim 20, wherein the mobile device is further configured to receive local information from a second mobile device.

Claim 30 (withdrawn): A method of re-broadcasting data transmitted over an FM subcarrier, comprising the steps of:

- receiving at a localcast transmitter said transmitted data;
- locally formatting said transmitted data for local-area wireless transmission; and
- retransmitting said locally formatted data from said localcast transmitter to a local area.

Claim 31 (withdrawn): The method of claim 30, further comprising the step of adding local content information in said localcast transmitter to said locally formatted data for transmission over a local area.

Claim 32 (withdrawn): The method of claim 30, further comprising the step of adding application information in said localcast transmitter to said locally formatted data for broadcast over a local area.

Claim 33 (withdrawn): The method of claim 30, further comprising the steps of receiving said locally formatted data at a first mobile device; and retransmitting said locally formatted data from the first mobile device to a second mobile device.

Claim 34 (withdrawn): A method of encoding a data stream, comprising the steps of:

- partitioning said data stream into a plurality of data packets at a transmission network center;
- transmitting said data packets to a broadcast generator;
- receiving said transmitted data packets at said broadcast generator;
- writing said received data packets into an I/O memory of said broadcast generator;

App. No. 10/044,294
Amendment Dated: May 6, 2004
Reply to Office Action of February 6, 2004

reading a plurality of extracted data packets from said I/O memory in an order that differs from the order in which said received data packets arrived at said I/O memory block; encoding said extracted data packets into encoded data streams; and interleaving said encoded data streams into a plurality of interleaved data segments.

Claim 35 (withdrawn): The method of claim 34, further comprising the steps of: determining whether a threshold amount of memory within said I/O memory has been filled by said received data packets; and initiating encoding of said received data packets if said determination is affirmative.

Claim 36 (withdrawn): The method of claim 34, further comprising the steps of: indicating, within each of said data packets whether each of said data packets requires lower-latency transmission time; and modifying said interleaving based on whether said data packets require lower-latency transmission time.

Claim 37 (withdrawn): The method of claim 34, the encoding further comprising the steps of: performing a bitwise-exclusive-OR between each bit of said extracted data packets and each bit of a data pattern to produce a plurality of whitened data streams; and convolutionally encoding said whitened data streams thereby producing said encoded data streams.

Claim 38 (withdrawn): A method of transmitting data, comprising the steps of: receiving a data stream including a plurality of data packets, wherein at least some data packets are designated as intended to be transmitted with low-latency; and

App. No. 10/044,294
Amendment Dated: May 6, 2004
Reply to Office Action of February 6, 2004

interleaving said data packets over a frame except that the data packets designated as intended to be transmitted with low-latency are interleaved over a sub frame of the broadcast frame.

Claim 39 (withdrawn): The method of claim 38, wherein said sub frame is one-fourth of said broadcast frame.

Claim 40 (previously amended): An apparatus for transmitting a signal in a wireless communications system including a data source, comprising:

a broadcast transmitter configured to transmit to a device over a subcarrier channel to a wide area; and

a localcast transmitter coupled to the data source and configured to transmit to a device over a local area and in a locally-unused FM frequency, wherein the device is:

configured to receive transmitted data from the localcast transmitter; and
further configured to receive transmitted data from a wide-area broadcast transmitter.

Claim 41 (previously amended): An apparatus for transmitting a signal in a wireless communications system including a data source, comprising:

a broadcast transmitter configured to transmit to a device over a subcarrier channel to a wide area; and

a localcast transmitter coupled to the data source and configured to transmit to and receive data from a device over a local area and in a locally-unused FM frequency, wherein the device is configured to receive the data from the localcast transmitter and to transmit other data to the localcast transmitter.

Claim 42 (previously amended): An apparatus for performing wireless communications, comprising:

a device configured to receive a wireless communication transmitted in a broadcast mode, wherein the broadcast mode includes data transmitted and received over an FM

App. No. 10/044,294
Amendment Dated: May 6, 2004
Reply to Office Action of February 6, 2004

subcarrier channel, the device being further configured to transmit and receive additional wireless communications transmitted in a localcast mode, wherein the localcast mode includes data transmitted and received over a locally-unused FM channel.

Claim 43 (cancelled)

Claim 44 (previously submitted): The system of claim 1, wherein the broadcast transmitter further comprises:

- an input-output controller that is coupled to a first input interface and to a buffer memory;
- a control processor that is coupled to the input-output controller and to a second input interface;
- a precision time base that is coupled to the control processor;
- an encoding engine that is coupled to the input-output controller, the control processor, and to a first memory; and
- a subcarrier signal generator that is coupled to the encoding engine, the control processor, a second memory, and to a subcarrier output.

Claim 45 (previously submitted): The system of claim 44, wherein the input-output controller is arranged to receive data from an uplink device via the first input interface.

Claim 46 (previously submitted): The system of claim 44, wherein the control processor is arranged to accept periodic commands and control information from an uplink device via the second input interface.

Claim 47 (previously submitted): The system of claim 44, wherein the precision time base is arranged to track a master time-base associated with an uplink device, whereby transmission delays are minimized.

App. No. 10/044,294
Amendment Dated: May 6, 2004
Reply to Office Action of February 6, 2004

Claim 48 (previously submitted): The system of claim 44, wherein the encoding engine is arranged to process frames of data received from an uplink device to produce an output image for transmission.

Claim 49 (previously submitted): The system of claim 44, wherein the subcarrier signal generator is arranged to receive an output image from the encoding engine and generate a subcarrier signal for transmitting the broadcast information over the subcarrier channel.

Claim 50 (currently amended): The apparatus of claim 42, wherein the localcast transmitter further comprises:

- a first interface;
- a control function that is coupled to the first interface, ~~said encoder and said packet assembler~~;
- an encoder that is coupled to the first interface and the control function;
- processing logic that is coupled to the encoder and the control function;
- a modulator that is coupled to the processing logic; and
- an antenna.

Claim 51 (previously submitted): The apparatus of claim 50, wherein the first interface is arranged to connect the localcast transmitter to its data source such that data packets are received by the localcast transmitter from the data source via the first interface.

Claim 52 (previously submitted): The apparatus of claim 50, wherein the control function is arranged to collect data packets via the first interface, perform handshaking between the localcast transmitter and a data source, and set a desired transmission frequency, a mode, and a signal power.

Claim 53 (previously submitted): The apparatus of claim 50, wherein the encoder is arranged to format data received from a data source as baseband samples, whereby encoding data for the localcast transmission is similar to encoding for broadcast transmission.

App. No. 10/044,294
Amendment Dated: May 6, 2004
Reply to Office Action of February 6, 2004

Claim 54 (previously submitted): The apparatus of claim 50, wherein the processing logic is arranged to add correlation information for synchronization to audio samples received from the encoder.

Claim 55 (previously submitted): The apparatus of claim 50, wherein the modulator is arranged to receive audio samples provided by the processing logic and produce an FM frequency output for transmitting data over a local area and in a locally-unused FM frequency.

Claim 56 (previously submitted): The apparatus of claim 42, wherein the device configured to receive a wireless communication further comprises:

- an antenna assembly;
- a real-time component comprising:
 - a system timing function;
 - a real-time event dispatching function; and
 - a digital radio;
- a digital control and processing circuit;
- a microcomputer assembly;
- a random access memory;
- a nonvolatile memory; and
- a microprocessor-controlled user interface.

Claim 57 (previously submitted): The apparatus of claim 42, wherein the device is further arranged to transmit and receive information from a second mobile device.

Claim 58 (previously submitted): The apparatus of claim 42, wherein the device is further arranged to receive information from a plurality of mobile devices and transmit data to a plurality of mobile devices.

App. No. 10/044,294
Amendment Dated: May 6, 2004
Reply to Office Action of February 6, 2004

Claim 59 (previously submitted): The apparatus of claim 42, wherein the device is further arranged to receive wireless communications transmitted in a localcast mode from a second mobile device.

Claim 60 (previously submitted): The apparatus of claim 42, wherein the device is further arranged to receive both the wireless communications transmitted in a localcast mode and the wireless communication transmitted in a broadcast mode using substantially the same circuitry.